



# LED BACKLIT PANEL



## PRODUCT FEATURES

- Tunable Wattage & CCT Models Available
- Seamless White Finish Frame
- Concave-Convex Edge Fold Aluminum Backplate
- Back-lit LED Technology
- PMMA Optic Anti-Yellow
- DLC Listed
- UL Listed
- 0-10V Dimming
- High Luminous Efficiency
- Glare-free Lighting
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range -4°F to 104°F (-20°C to 40°C)

## PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (FT)	EFFICIENCY (lm/W)	BEAM ANGLE
CLP99-2X2BLP-29W40K	L2X2B29W4KCLP99	29	3190	4000	2 X 2	110	120°
CLP99-2X2BLP-29W50K	L2X2B29W5KCLP99	29	3190	5000	2 X 2	110	120°
CLP99-2X4BLP-49W40K	L2X4B49W4KCLP99	49	5300	4000	2 X 4	108	120°
CLP99-2X4BLP-49W50K	L2X4B49W5KCLP99	49	5300	5000	2 X 4	108	120°
CLP99-2X2BLP-15/19/24/29W-30K-40K-50K <b>TUNABLE WATTAGE &amp; CCT</b>	L2X2BTUNCLP99	15	1950	3000	2 X 2	130	120°
		19	2470	4000			
		24	3120	5000			
		29	3770	5000			
CLP99-2X4BLP-29/34/39/49W-30K-40K-50K <b>TUNABLE WATTAGE &amp; CCT</b>	L2X4BTUNCLP99	29	3770	3000	2 X 4	130	120°
		34	4420	4000			
		39	5070	5000			
		49	6370	5000			

