



LED BYPASS MODE TUBES



PRODUCT FEATURES

- Retrofit / Bypass Mode - Double Ended (Type B)
- Existing Fixture is Wired to Bypass the Ballast
- Film Coated Shatter Resistant Glass Tube
- Frosted
- Instant On / No Flicker
- 1-10% Dimming
- No Mercury, Lead Free
- No UV Emission
- Low Maintenance
- 120-277 Voltage Rating
- Fa8 Mounting
- DLC Listed
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operational Temperature Range: -4°F to 113°F (-20°C to 45°C)

PRODUCT SPECIFICATIONS

| MODEL | ITEM # | POWER (W) | LUMENS (LM) | CCT (K) | LENGTH (IN) | EFFICIENCY (Lm/W) | BEAM ANGLE |
|-----------------------|--------------|-----------|-------------|---------|-------------|-------------------|------------|
| CLT93-42WT8 840-8FT-B | L42T84KBCL93 | 42 | 5400 | 4000 | 96.0 | 128 | 240° |
| CLT93-42WT8 850-8FT-B | L42T85KBCL93 | 42 | 5500 | 5000 | 96.0 | 130 | 240° |

