



## LED BYPASS MODE TUBES



### PRODUCT FEATURES

- Retrofit / Bypass Mode - Double and Single Ended (Type B)
- Bypass installation utilizes existing lamp holders
- Film Coated Shatter Resistant Glass Tube
- Frosted
- Instant On / No Flicker
- Non-Dimming
- IP20 Rated
- 120-277 Voltage Rating, PF > 0.9
- 80+ CRI
- G13 Mounting
- Aluminum End Caps
- UL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature: -4°F to 113°F (-20°C to 45°C)

### PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	LENGTH (IN)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLT94-15WT8AM-40-B	L15T84KBCL94	15	1900	4000	48.0	127	220°
CLT94-15WT8AM-50-B	L15T85KBCL94	15	1900	5000	48.0	127	220°
CLT94-18WT8AM-40-B	L18T84KBCL94	18	2200	4000	48.0	122	220°
CLT94-18WT8AM-50-B	L18T85KBCL94	18	2200	5000	48.0	122	220°

