




LED DUAL MODE TUBES



PRODUCT FEATURES

- Direct Replacement / Plug & Play Mode (Type A) *
- Retrofit / Bypass Mode - Double and Single Ended (Type B)
- Works with shunted or un-shunted sockets when double end bypassed.
- IP40 Rating
- Non-Dimming
- Low Thermal Decay
- 100-277 Voltage Rating
- Film Coated Shatter Resistant Glass Tube
- Frosted
- 50,000 Hour Lifetime Rating
- NSF Certified
- UL Certified
- G13 Mounting
- Low Maintenance
- No Mercury, Lead Free
- No UV Emission
- 5-Year Limited Warranty
- Operating Temperature Range: -4°F to 122°F (-20°C to 50°C)

* See Ballast Compatibility Chart

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	LENGTH (IN)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLT99-15WT8FG-40-AB	L15T84KABCL99	15	1900	4000	48.0	127	240°
CLT99-15WT8FG-50-AB	L15T85KABCL99	15	1900	5000	48.0	127	240°
CLT99-17WT8FG-40-AB	L17T84KBACL99	17	2300	4000	48.0	136	240°
CLT99-17WT8FG-50-AB	L17T85KBACL99	17	2300	5000	48.0	136	240°
CLT99-17WT8FG-35-AB	L17T835KBACL99	17	2150	3500	48.0	126	240°

